



3Gx1.5mm² x2m, C14 Plug

PDU Technology Specification

Date : 30/10/2014

NO:

Customer			
Product Name	Designated Power Distribution Unit for Cabinet	Customer's code	STT19-8USV
Part Number	TUL-GER(16)N1008WGZB19A	Picture code	
No.	Item	Detailed Description	
1	Product Series	1U	
2	Socket Type	DIN49440(red)	
3	Output Unit	DIN49440	
4	Power Input	Left single input	
5	Bracket Install	Horizontal install	
6	Cable with plug	IEC320 C14	
7	Control Function	None	
8	Protection Function	Overload Switch	
9	Shell Color	Black	
10	Cable Specification	H05VV-F3G×1.5mm ² ×2m	
11	Product Size	L×W×H=485×44.45×44.45mm	
12	Mounting Length	464mm	
13	Case Length	435mm	
14	Fittings	Two φ6×16mm cross bolt 、 two M6 fluctuation nut、 PDU instruction handbook (choice)	
15	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	16A
		Max. Power	3500W
		Safety Authentication	CE. RoHS.
		Logo	
Producer	Ningbo Turn-link Communication Equipment Co.,LTD		
No.	Add-In		
1	Socket assemble	Overload,DIN49440	
2	Interior Connection Wire	2.5mm ² Brass strip	
3	Interior Connection Style		
4	Fix the Cable	Screw fix without spot	
5	Module Assemble (From left to right)	Overload ,8DIN49440	
6	Others		

Made by:	Customer confirm:	Check:	Authorize:
-----------------	--------------------------	---------------	-------------------

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.